

## PERFECT Style 340



### PRODUCT DESCRIPTION

High strength ARAMID synthetic yarn with each strand fully impregnated with PTFE & high temperature resisting lubricants. The packing has flexibility, resiliency, and lubricity with excellent thermal and dimensional stability, treating the shaft gently.

### SERVICE PARAMETERS

#### Maximum Service Temperature:

-240 to +260 ° C

#### Compatible pH Range:

2 to 12 ph range

#### Pressure Rating:

250

#### Velocity

12 Mtrs/sec.

### SERVICE

For abrasive media slurry applications in valves, mixers, agitators, rotary and reciprocatory applications in solvents, mild acids and alkalies petrochemicals, paper and pulp and pharmaceuticals.

*Information supplied this catalogue, is based on our general experience and is given in good faith, because of the many particular factors, which are out side of our knowledge and control and affect the use of products, nowarranty is given is to be implied with respect to such information.*

## PERFECT Packing Industries

19/A Revabhai Industrial Estate, C.T.M Cross Road,  
Amraiwadi, Ahmedabad-380026(Gujarat-India)  
Ph No.079-25857824  
Fax No. 079-28587871

[www.perfectpacking.com](http://www.perfectpacking.com)  
[info@perfectpacking.com](mailto:info@perfectpacking.com)

DISTRIBUTED BY: