

## PERFECT Style 378



### PRODUCT DESCRIPTION

A unique braided packing made from Graphite bonded PTFE yarn with aramid corners.

### SERVICE PARAMETERS

#### Maximum Service Temperature:

-240 to +260 ° C

#### Compatible pH Range:

2 to 12 ph range

#### Pressure Rating:

200

#### Velocity

20 Mtrs/sec.

### SERVICE

This packing is a combination of especially Graphite bonded PTFE Yarn and aramid yarn, impregnated with special mix. It has a high structure strength and density. The presence of Graphite bonded PTFE Yarn is a reason for excellent chemical stability to aggressive environments and good sealing properties. It is widely used in chemical and petrochemical plants, power engineering, cement, cellulose and sugar industries, shipbuilding, drinking water, abrasive solutions, oil products, oils, fats, acid and alkaline solutions, food solutions and pastes. etc.

*Information supplied this catalogue, is based on our general experience and is given in good faith, because of the many particular factors, which are out side of our knowledge and control and affect the use of products, nowarranty is given is to be implied with respect to such information.*

## PERFECT Packing Industries

19/A Revabhai Industrial Estate, C.T.M Cross Road,  
Amraiwadi, Ahmedabad-380026(Gujarat-India)  
Ph No.079-25857824  
Fax No. 079-28587871

[www.perfectpacking.com](http://www.perfectpacking.com)  
[info@perfectpacking.com](mailto:info@perfectpacking.com)

DISTRIBUTED BY: