

## PERFECT Style Asbestos Yarn



### PRODUCT DESCRIPTION

The coarse yarn is an excellent variety, which has varied usage and has sufficient tensile strength.

### SERVICE PARAMETERS

**Maximum Service Temperature:**

350 °C

**Compatible pH Range:**

-

**Pressure Rating:**

-

**Velocity**

-

### SERVICE

It is used in lagging small pipes, low pressure packing and as a jointing medium in patent glazing. It has a great utility in manufacturing Asbestos Cloth, Webbing, Plaited Packing, Steam Hoses, Break Linings & Clutch facings etc.

### Sizes & Standard Packing:-

Thickness: 1.5 mm to 6 mm  
1 Kg. spools in HDPE bag of 50 Kg. each.

*Information supplied this catalogue, is based on our general experience and is given in good faith, because of the many particular factors, which are out side of our knowledge and control and affect the use of products, nowarranty is given is to be implied with respect to such information.*

## PERFECT Packing Industries

DISTRIBUTED BY:

19/A Revabhai Industrial Estate, C.T.M Cross Road,  
Amraiwadi, Ahmedabad-380026(Gujarat-India)  
Ph No.079-25857824  
Fax No. 079-28587871

www.perfectpacking.com  
info@perfectpacking.com